

MECHANICAL REDUCER chain + belt transmission

RUNNING SPEED





AMATEUR



| | 4 | | 7 |
|---|---|---|---|
| K | U | τ | Z |

Euro B&S Honda Euro **GP160** 182.ohv R210.ohv CR950 163 cc **ENGINE** 182 cc 212 cc 208 cc 3.1 kW 4.2 kW 4.0 kW 3.6 kW Petrol Petrol Petrol Petrol

STARTER recoil

vertically vertically vertically vertically **HANDLEBAR** and laterally and laterally adjustable adjustable adjustable adjustable

gears, chain in oil bath and double belt system 1 fixed milling speed, reverse **TRANSMISSION**

4 stars Ø32 cm - 16 riveted knives

ROTAVATOR work width 50 cm

270 rpm

adjustable spur **OTHER** system for quick visual inspection of correct belt tensioning

tyres, tractor profile 13x5.00-6" **DRIVE WHEELS** with mechanical transport idler

66 kg 67 kg 66.5 kg **NET WEIGHT** 65 kg

DIMENSIONS 53X151X109(h) cm

GR.WEIGHT 71-73 KG

PACKAGING 116,5X53X70(H) CM

110X120X225(H) CM / Q* 6PCS PALLET







SMALL ROTAVATOR cutter 32 cm iron wheels Ø35x5



RIDGING PLOW with fixed wings



AS STANDARD



OPTIONAL



PATENTED