

Carry

wheel barrow

MECHANICAL REDUCER
belt transmission



RUNNING SPEED

2.0 km/h  3.6 km/h

1.7 km/h  3.0 km/h

Carry 24v

AMATEUR



Carry

Carry BATTERY

	B&S 450 E series	Euro 123.ohv	Honda GCVx170	Euro R170.ohv	Euro Battery	NEW EGOpower+ e-powered
ENGINE	125 cc 1.8 kW Petrol	123 cc 2.2 kW Petrol	166 cc 3.6 kW Petrol	173 cc 3.2 kW Petrol	24 V 300 W Electric	56 V 3.1 kW Electric
STARTER	recoil				electric	
TRANSMISSION	endless screw in oil bath and belts 1 forward gear, reverse gear				endless screw in oil bath and belts 1 forward gear, reverse gear	
TANK	tilting galvanised sheet metal tank max. capacity 85 lt max. load-bearing capacity 100 kg				tilting galvanised sheet metal tank max. capacity 85 lt max. load-bearing capacity 100 kg	
OTHER	-				2 lead batteries 12V 5Ah each	optional lithium batteries
DRIVE WHEELS	tractor profile front tyres 13x5.00-6" with mechanical semi-differential				tractor profile front tyres 13x5.00-6" with mechanical semi-differential	
NET WEIGHT	57 kg	60 kg	60 kg	58 kg	93 kg	61 kg
DIMENSIONS	65x145x100(h) cm				65x145x100(h) cm	

	GR.WEIGHT	62-64 KG
	PACKAGING	110X65X70(H) CM
	PALLET	114X134X225(H) CM / Q* 6PCS

GR.WEIGHT	99-66 KG
PACKAGING	110X65X70(H) CM
PALLET	130X114X155(H) CM / Q* 4PCS



DRIVE WHEELS
tractor profile with
mechanical semi-
differential



TILTING TANK
through lever on the
handlebar handle



REAR WHEELS
pivoting on floating axle



TANK EXTENSION
140 l capacity
fast coupling



FLAT TANK
capacity 160 l
+ sheet metal
platform



SNOW BLADE
85 cm, adjustable
laterally $\pm 30^\circ$



REAR WHEELS
pneumatics



AS STANDARD



ACCESSORY



PATENTED