

SOIL

Rtt3

rear tine tiller

MECHANICAL GEARBOX
chain + belt transmission



RUNNING SPEED

1.8 Km/h 2.1 Km/h
1.0 Km/h 1.1 Km/h



SEMI-PROFESSIONAL



Rtt3

	Euro	Euro	B&S	Honda
ENGINE	212.ohv 212 cc 4.0 kW Petrol	R210.ohv 212 cc 4.4 kW Petrol	CR950 208 cc 4.0 kW Petrol	GX160 163 cc 3.6 kW Petrol

STARTER recoil

HANDLEBAR	vertically adjustable	vertically adjustable	vertically and laterally adjustable	vertically and laterally adjustable
------------------	-----------------------	-----------------------	-------------------------------------	-------------------------------------

TRANSMISSION  gears, chain in oil bath and double belt system
2 speed fixed milling, 2 speed reverse

TILLER 6 stars Ø32 cm - 20 bolted knives
work width 60 cm
270 rpm

OTHER adjustable spur
system for quick visual inspection of correct belt tensioning

DRIVE WHEELS tyres, tractor profile 13x5.00-6"
with mechanical transport idler

NET WEIGHT	72 kg	72 kg	70.5 kg	70 kg
-------------------	-------	-------	---------	-------

DIMENSIONS 63x153x109(h) cm

 GR.WEIGHT	75-77 KG
 PACKAGING	116,5X53X70(H) CM
 PALLET	110X120X225(H) CM / Q* 6PCS



HANDLEBAR
vertically and laterally
adjustable
** B&S / Honda only*



TOOL COUPLING LEVER
with visual drive belt
tensioning control system



ROTAVATOR
bolted knives
Ø32 cm 60 cm



DRIVEN WHEELS
with mechanical semi-
differential



SMALL ROTAVATOR
cutter 32 cm
iron wheels Ø35x5



RIDGING PLOW
with fixed wings



AS STANDARD



ACCESSORY



PATENTED